


# Vibra-Sandmaster (with Verti-Quake)

The Vibra-Sandmaster de-compacts & adds surface drainage to the soil profile all in one pass. Integrated within the Vibra-Sandmaster is the Verti-Quake® 2516, this de-compacts and opens the soil to depth of 250 mm. Vibrating coulters fill the slits with sand to leave minimal surface disruption.



## Specifications

SKU	115.251.502
Working width (m)	1.56
Working width (inch)	61.4
Max. Working depth (mm)	125-200
Max. Working depth (inch)	4.9 - 7.9
Hopper capacity (m3)	1.5
Hopper capacity (FT3)	53
Weight (kg)	2035 (without Verti-Quake 2516) / 2650 (with Verti-Quake 2516)
Weight (lbs)	4486 (without Verti-Quake 2516) / 5842 (with Verti-Quake 2516)
Number of filling coulters	6
Distance between filling coulters (mm)	260
Distance between filling coulters (inch)	10,236
Thickness of filling coulters (mm)	25
Min. Tractor HP required	65-90 with four-wheel drive
Max. capacity ( m² hr)	1000
Max. capacity (ft² hr)	10800
Min. Oil supply of tractor (l min)	30
Min. Oil supply of tractor (US Gal min)	7.9
Required connections	1 x single-acting (lifting machine)1 x double-acting valve (conveyor belt)
Rpm Max.	540
Lubricant	EP2 + High grade grease HT Q9