© 2024 Redexim United Kingdom https://www.redexim.com/uk

# Multi-Seeder 1600

The floating twin spike rollers of the Multi-Seeder follow the contours, saturating the surface with small holes. the seed is then accurately distributed onto the surface before an adjustable brush sweeps the seeds into the holes. The rear roller then passed over to cover the seed for germination.

Image not found or type unknown



**Specifications**

| | |
|---|---|
| SKU | 124.160.004 |
| Operation | Tractor pulled |
| Working width (m) | 1.6 |
| Working width (inch) | 63 |
| Max. Working depth (mm) | 5 - 20 |
| Max. Working speed (km h) | 12 |
| Max. Working speed (mph) | 7.5 |
| Weight (kg) | 750 |
| Weight (lbs) | 1653 |
| Hopper capacity (L) | 200 |
| Hopper capacity (cu.ft.) | 7.1 |
| Min. Tractor HP required | 35 |
| Min. Lifting capacity 610 mm behind the lifting eyes (kg) | 1280 |
| Min. Lifting capacity 24 inch behind the lifting eyes (lbs) | 2822 |
| Min. Pressure (bar) | 1 - 2 |
| Min. Pressure (psi) | 14.5 - 29 |
| Three-point hitch | 3-point CAT 1-2 |
| Lubricant | EP2 |