


The Multi Spike opens the surface of sports turf, fairways, tees or greens in order to move air, water and nutrients into the soil. The different size knife options available make configuring the Multi-Spike for exact turf conditions easy. The optional bogie kit allows the Multi-Spike to be towed.





Vorking width (m)1.35Vorking width (inch)56Max. Working depth (mm)250Max. Working depth (inch)10Veight (kg)400Veight (lbs)880Slit distance between the knives (mm)150Slit distance between the knives (inch)6Hole spacing distance driving direction (mm)330Hole spacing distance driving direction (inch)13	.120.000 5
Vorking width (inch)56Max. Working depth (mm)250Max. Working depth (inch)10Veight (kg)400Veight (lbs)880Slit distance between the knives (mm)150Slit distance between the knives (inch)6Hole spacing distance driving direction (mm)330Hole spacing distance driving direction (inch)13	5
Max. Working depth (mm)250Max. Working depth (inch)10Veight (kg)400Veight (lbs)880Slit distance between the knives (mm)150Slit distance between the knives (inch)6Hole spacing distance driving direction (mm)330Hole spacing distance driving direction (inch)13	
Max. Working depth (inch)10Veight (kg)400Veight (lbs)880Slit distance between the knives (mm)150Slit distance between the knives (inch)6Hole spacing distance driving direction (mm)330Hole spacing distance driving direction (inch)13	
Veight (kg)400Veight (lbs)880Slit distance between the knives (mm)150Slit distance between the knives (inch)6Hole spacing distance driving direction (mm)330Hole spacing distance driving direction (inch)13	
Veight (lbs)880Slit distance between the knives (mm)150Slit distance between the knives (inch)6Hole spacing distance driving direction (mm)330Hole spacing distance driving direction (inch)13	
Slit distance between the knives (mm)150Slit distance between the knives (inch)6Hole spacing distance driving direction (mm)330Hole spacing distance driving direction (inch)13	
Slit distance between the knives (inch)6Hole spacing distance driving direction (mm)330Hole spacing distance driving direction (inch)13	
Hole spacing distance driving direction (mm)330Hole spacing distance driving direction (inch)13	
Iole spacing distance driving direction (inch) 13	
······································	
In. Tractor HP required 18	
Ain. Lifting capacity 610 mm behind the lifting eyes (kg)500	
/in. Lifting capacity 24 inch behind the lifting eyes (lbs) 110	0
Aax. capacity (m ² hr) 675	0
Aax. capacity (ft ² hr) 600	00
Three-point hitch 3-pc	vint CAT 1-2
ubricant EP 2	2
imited availability 1	