


The DS3100 Evo has a large hopper capacity of 3.1m3 (110cu.ft). The internal conveyor belt moves wet or dry material to the rear of the hopper where it is dropped onto the discs for spreading up to 12m (472") an automatic rear gate opens & closes to prevent material being dropped in transit





## **Specifications**

| Specifications                          |                                  |
|---|----------------------------------|
| SKU                                     | 133.310.001                      |
| Operation                               | Towed version                    |
| Spreading width (mm)                    | up to 12000                      |
| Spreading width (inch)                  | up to 472                        |
| Hopper capacity (m3)                    | 3.1                              |
| Hopper capacity (FT3)                   | 109.5                            |
| Max. Working speed (km h)               | 25                               |
| Max. Working speed (mph)                | 16                               |
| Min. Tractor HP required                | 45                               |
| Min. Oil supply of tractor (I min)      | 25                               |
| Min. Oil supply of tractor (US Gal min) | 6.6                              |
| Min. Pressure (bar)                     | 140                              |
| Min. Pressure (psi)                     | 2031                             |
| Required connections                    | 1x Double-acting hydraulic valve |
| Empty Weight (kg)                       | 1300                             |
| Empty Weight (lbs)                      | 2866                             |
| Spreading width up to (mm)              | 12000                            |
| Spreading width up to (inch)            | 472                              |
|   |                                  |