


# Rink DS800 Trailed

The Rink DS800 disc spreader distributes a range of material, the integrated transport belt moves wet or dry material to the rear of the machine to be spread by the twin discs. The spreading width & thickness can easily be adjusted. The rear door closes to prevent material spillage in transport.



## Specifications

|                                         |                                  |
|-----------------------------------------|----------------------------------|
| SKU                                     | 133.080.002                      |
| Operation                               | Towed version                    |
| Spreading width (mm)                    | up to 12000                      |
| Spreading width (inch)                  | up to 472                        |
| Hopper capacity (FT3)                   | 28.3                             |
| Max. Working speed (km h)               | 25                               |
| Max. Working speed (mph)                | 16                               |
| Min. Tractor HP required                | 25                               |
| Min. Oil supply of tractor (l min)      | 25                               |
| Min. Oil supply of tractor (US Gal min) | 6.6                              |
| Min. Pressure (bar)                     | 140                              |
| Min. Pressure (psi)                     | 2030.52                          |
| Required connections                    | 1x Double-acting hydraulic valve |
| Empty Weight (kg)                       | 460                              |
| Empty Weight (lbs)                      | 1014                             |
| Spreading width up to (mm)              | 12000                            |
| Spreading width up to (inch)            | 472                              |