


Turf-Stripper 1200

The Turf-Stripper 1200 with interchangeable rotors will remove turf, weeds and thatch from a different turf surfaces including hybrid turf areas (with the optional hybrid rotor). A side arm conveyor transfers the debris into a trailer for easy removal from the surface and a clean finish





Specifications

| Specifications | |
|-------------------------------------------------------------|-------------------------|
| SKU | 153.120.000 |
| Working width (m) | 1.2 |
| Working width (inch) | 47.2 |
| Max. Working depth (mm) | 50 |
| Max. Working depth (inch) | 2 |
| Drain height (mm) | 1500 |
| Drain height (inch) | 59 |
| Max. Working speed (km h) | 3 |
| Max. Working speed (mph) | 1.8 |
| Weight (kg) | 620 |
| Weight (lbs) | 1367 |
| Min. Tractor HP required | 30-40 |
| Min. Lifting capacity 610 mm behind the lifting eyes (kg) | 775 |
| Min. Lifting capacity 24 inch behind the lifting eyes (lbs) | 1709 |
| Required connections | 1 x Double-acting valve |
| Three-point hitch | 3-point CAT 1 |
| Rpm Max. | 540 |
| Gearbox oil | SAE 140 |
| Lubricant | EP2 |
| | |