

# Verti-Drain® 7212

The Verti-Drain® 7212 is well suited to lower HP tractors, this very capable model for aeration to a depth of 10" /25cm on the more sensitive turf areas. The 7212 is particularly popular on hard to reach areas due to its overall dimensions while maintaining all the features of larger Verti-Drains.



## Specifications

|                                                             |                      |
|-------------------------------------------------------------|----------------------|
| SKU                                                         | 7212                 |
| Working width (m)                                           | 1.2                  |
| Working width (inch)                                        | 48                   |
| Max. Working depth (mm)                                     | 250                  |
| Max. Working depth (inch)                                   | 10                   |
| Working speed at hole spacing 65 mm (km h)                  | 1                    |
| Weight (kg)                                                 | 470                  |
| Weight (lbs)                                                | 1030                 |
| Hole distance with 12 mm tines (mm)                         | 65                   |
| Hole distance with 1 2 x 6 inch tines (inch)                | 2.5                  |
| Hole distance with 18 mm tines (mm)                         | 100                  |
| Hole distance with 3 4 x 9 inch tines (inch)                | 4                    |
| Hole spacing distance driving direction (mm)                | 25 - 165             |
| Hole spacing distance driving direction (inch)              | 1 - 6-1/2            |
| Max. Diameter solid tine (mm)                               | 18 x 250             |
| Max. Diameter solid tine (inch)                             | 3/4 x 10             |
| Max. Diameter hollow tine (mm)                              | 25 x 250             |
| Max. Diameter hollow tine (inch)                            | 1 x 10               |
| Min. Tractor HP required                                    | 18                   |
| Min. Lifting capacity 610 mm behind the lifting eyes (kg)   | 570                  |
| Min. Lifting capacity 24 inch behind the lifting eyes (lbs) | 1250                 |
| Max. capacity with spacing 65 mm (m² hr)                    | 1200                 |
| Max. capacity with spacing 2 1 2 inch (ft² hr)              | 11000                |
| Three-point hitch                                           | 3-point CAT 1        |
| Rpm Max.                                                    | 500                  |
| Gearbox oil                                                 | 80W90 3 liter        |
| Lubricant                                                   | EP 2                 |
| Dimensions (width mm)                                       | 1350                 |
| Dimensions (height mm)                                      | 800                  |
| Dimensions (length mm)                                      | 1100                 |
| Dimensions (width inch)                                     | 44                   |
| Dimensions (height inch)                                    | 32                   |
| Dimensions (length inch)                                    | 54                   |
| Slip clutch setting                                         | 450 NM (3983 lbf-in) |