

Vibra-Sandmaster (with Verti-Quake)

The Vibra-Sandmaster de-compacts & adds surface drainage to the soil profile all in one pass. Integrated within the Vibra-Sandmaster is the Verti-Quake® 2516, this de-compacts and opens the soil to depth of 250mm. Vibrating coulters fill the slits with sand to leave minimal surface disruption.



Specifications	
SKU	115.251.502
Working width (m)	1.56
Working width (inch)	61.4
Max. Working depth (mm)	125-200
Max. Working depth (inch)	4.9 - 7.9
Hopper capacity (m3)	1.5
Hopper capacity (FT3)	53
Weight (kg)	2650
Weight (lbs)	5842
Number of filling coulters	6
Distance between filling coulters (mm)	260
Distance between filling coulters (inch)	10,236
Thickness of filling coulters (mm)	25
Min. Tractor HP required	65-90 with four-wheel drive
Max. capacity (m ² hr)	1000
Max. capacity (ft ² hr)	10800
Min. Oil supply of tractor (l min)	30
Min. Oil supply of tractor (US Gal min)	7.9
Required connections	1 x Double-acting valve (elevating the machine) 2 x Double-acting valves (conveyor drive)
Rpm Max.	540
Lubricant	EP2 + High grade grease HT Q9