

Verti-Drain® 7117

The Verti-Drain® 7117 offers speed for a high output while remaining compact. The 7117 is ideal for golf greens, tees and approaches. The optional Turf Hold Down Kit ensures the turf is protected during the aeration process.



Specifications	
SKU	7117
Working width (m)	1.7
Working width (inch)	68
Max. Working depth (mm)	150
Max. Working depth (inch)	6
Working speed at hole spacing 65 mm	2.36
Working speed at hole spacing 2-1 2 inch (mph)	1.48
Weight (kg)	631
Weight (lbs)	1388
Hole distance with 12 mm tines (mm)	55
Hole distance with 1 2 x 6 inch tines (inch)	2.16
Hole spacing distance driving direction (mm)	25 - 125
Hole spacing distance driving direction (inch)	1-5
Max diameter solid tine (mm)	12 x 150
Max diameter solid tine (inch)	1/2 x 6
Max diameter hollow tine (mm)	19 x 150
Max diameter hollow tine (inch)	3/4 x 6
Min. Tractor HP required	28
Min. lifting capacity (kg)	700
Min. lifting capacity (LBS)	1550
Max. capacity with spacing 65 mm (m ² hr)	3900
Max. capacity with spacing 2-1 2 inch (ft ² hr)	34863
Three-point hitch	3-point CAT 1
Rpm Max.	500
Gearbox oil	80W90 - 3liter
Lubricant	Ep 2
Dimensions (width mm)	1900
Dimensions (height mm)	750
Dimensions (length mm)	1050
Dimensions (width inch)	76
Dimensions (height inch)	30
Dimensions (length inch)	42
Slip clutch setting	450 NM (3983 lbf-in)