

Verti-Drain® 7516

The Verti-Drain® 7516 packs a punch while remaining compact. Capable of working to a depth of 40cm / 16", the 7516 is well suited to work on sport fields, golf course and with municipalities. The tough chassis makes it the ideal Verti-Drain for a range of aeration tasks no more challenging ground



Specifications

| | |
|--|-----------------|
| SKU | 7516 |
| Working width (m) | 1.6 |
| Working width (inch) | 63 |
| Max. Working depth (mm) | 400 |
| Max. Working depth (inch) | 16 |
| Weight (kg) | 1130 |
| Weight (lbs) | 2490 |
| Hole distance with 12 mm tines (mm) | 65 |
| Hole distance with 1 2 x 6 inch tines (inch) | 2.5 |
| Hole distance with 24 mm tines (mm) | 129 |
| Hole distance with 1 x 16 inch tines (inch) | 5 |
| Hole spacing distance driving direction (mm) | 50-195 |
| Hole spacing distance driving direction (inch) | 2 - 7-1/2 |
| Max diameter solid tine (mm) | 24 x 400 |
| Max diameter solid tine (inch) | 1 x 16 |
| Max diameter hollow tine (mm) | 32 x 300 |
| Max diameter hollow tine (inch) | 1-1/4 x 12 |
| Min. Tractor HP required | 45 |
| Min. lifting capacity (kg) | 1350 |
| Min. lifting capacity (LBS) | 3000 |
| Max. capacity with spacing 65 mm (m ² hr) | 1120 |
| Max. capacity with spacing 2-1 2 inch (ft ² hr) | 10200 |
| Three-point hitch | 3-point CAT 1-2 |
| Rpm Max. | 500 |
| Gear case oil | 80W90 - 5.8 |
| Lubricant | EP 2 |
| Slip clutch setting | 800 Nm |