


# Laser-Grader 1500TPP dual pole

The Laser-Grader 1500 TPP has a 6.5 hp engine to power the hydraulic system independently from the towing unit. Dual PVG16 valves are fitted as standard to allow the machine to be controlled to a dual laser receiver for the most accurate control of the working depths and a perfectly level finish



## Specifications

SKU	192.150.006
Engine	6.5 HP B&S
Operation	Tractor or bunker rake pulled
Working width (m)	1.5
Working width (inch)	59.9
Max. Working depth (inch)	Depending on the conditions and the required result
Hopper capacity (m3)	Depending on the conditions and the required result
Max. Working speed (km h)	Depending on the conditions and the required result
Max. Working speed (mph)	Depending on the conditions and the required result
Weight (kg)	406
Weight (lbs)	895
Number of tines	6 ripping tines
Hydraulic oil	Tellus 46
Content of the hydraulic oil tank	15litres ( 0.52 cu.ft)
Min. Tractor HP required	n/a – suitable towing vehicle
Min. Pressure (bar)	1.5
Min. Pressure (psi)	21.75
Lubricant	EP 2
Dimensions (width mm)	1.5
Dimensions (height mm)	1.2
Dimensions (length mm)	2.5
Dimensions (width inch)	59
Dimensions (height inch)	47.1
Dimensions (length inch)	98.4