

## Rink DS1200 Hybrid

The Rink DS1200 Hybrid has an internal conveyor belt which moves wet or dry material to the rear of the hopper where it is dropped onto the discs for spreading up to 12m (472'). The automatic rear gate opens & closes to prevent material being dropped when in transport ensuring no mess



### Specifications

|   |                                  |
|---|----------------------------------|
| SKU                                     | S0001579                         |
| Operation                               | Towed version                    |
| Spreading width up to (mm)              | 12000                            |
| Spreading width up to (inch)            | 472                              |
| Hopper capacity (m3)                    | 1.2                              |
| Hopper capacity (FT3)                   | 42.4                             |
| Max. Working speed (km h)               | 25                               |
| Max. Working speed (mph)                | 16                               |
| Spreading thickness (mm)                | 0.3 - 20                         |
| Spreading thickness (inch)              | 0.01 - 0.79                      |
| Min. Tractor HP required                | 27                               |
| Min. Oil supply of tractor (l min)      | 25                               |
| Min. Oil supply of tractor (US Gal min) | 6.6                              |
| Min. Pressure (bar)                     | 140                              |
| Min. Pressure (psi)                     | 2031                             |
| Required connections                    | 1x Double-acting hydraulic valve |
| Empty Weight (kg)                       | 490                              |
| Empty Weight (lbs)                      | 1080                             |