


## Verti-Drain® 7316

The Verti-Drain® 7316 is a highly versatile machine, popular in sports fields, golf & municipality settings, it can handle the tougher conditions while remaining suitable for smaller chassis tractors. The three-speed gearbox makes it easy to further adjust the working speed for a perfect finish



### Specifications

SKU	S0001503
Operation	Tractor Mounted
Working width (m)	1.6
Working width (inch)	63
Max. Working depth (mm)	300
Max. Working depth (inch)	12
Working speed at hole spacing 65 mm (km h)	0.85
Working speed at hole spacing 2 1 2 inch (mph)	0.55
Weight (kg)	670
Weight (lbs)	1480
Hole distance with 12 mm tines (mm)	65
Hole distance with 1 2 x 6 inch tines (inch)	2.5
Hole distance with 18 mm tines (mm)	130
Hole distance with 3 4 x 9 inch tines (inch)	5
Hole spacing distance driving direction (mm)	25 - 195
Hole spacing distance driving direction (inch)	1 - 7-1/2
Max. Diameter solid tine (mm)	18 x 300
Max. Diameter solid tine (inch)	3/4 x 12
Max. Diameter hollow tine (mm)	25 x 250
Max. Diameter hollow tine (inch)	1 x 10
Min. Tractor HP required	35
Min. Lifting capacity 610 mm behind the lifting eyes (kg)	825
Min. Lifting capacity 24 inch behind the lifting eyes (lbs)	1815
Max. capacity with spacing 65 mm (m <sup>2</sup> hr)	1360
Max. capacity with spacing 2 1 2 inch (ft <sup>2</sup> hr)	12300
Three-point hitch	3-point CAT 1
Rpm Max.	500
Gear case oil	80W90 - 5
Lubricant	EP 2
Slip clutch setting	500 Nm